

FORK OIL EXPERT LIGHT 5W

Fluido hidráulico para todo tipo de Horquillas telescópicas
Hydraulic Fluids for any type of telescopic forks
Technosynthese®

CONSEILS D'UTILISATIONS

Specially designed for any type of fork, upside-down ("USD") forks or conventional ("right-side-up») forks.

PERFORMANCES

Specific Technosynthese® formulation that contains exclusive anti-friction additive specially developed by MOTUL to create easier sliding and to avoid drag in the fork.

Stable absorption trough extended range of temperature thanks to the use of synthetic base stocks.

Seals protection: excellent lubricant / elastomer compatibility.

Anti-wear, anti-corrosion, anti-foaming.

RECOMMANDATIONS

MOTUL Fork Oil Expert can be mixed to obtain the required absorption effect. Use the exact quantity recommended by the fork manufacturer.

PROPRIÉTÉS

Densité à 20°C	ASTM D1298	0.844
Viscosité à 40°C (104°F)	ASTM D445	18.9 mm ² /s
Viscosité à 100°C (212°F)	ASTM D445	4.0 mm ² /s
Indice de viscosité	ASTM D2270	108.0 108
Point éclair	ASTM D92	198.0 °C / 388.0 °F
Point d'écoulement	ASTM D97	-42.0 °C / -44.0 °F

Nous nous réservons le droit de modifier les caractéristiques générales de nos produits pour faire bénéficier notre clientèle de l'évolution de la technique.

Les spécifications de nos produits ne sont définitives qu'à compter de la commande laquelle est soumise à nos conditions générales de vente et de garantie.